



Product Description: Pitch:5.0mm Rated
Voltage : 320V Rated Current:10A
colour : customizable

Technical drawing of the 100mm x 100mm x 10mm aluminum plate. The drawing includes three views: a top view, a front view, and a side view. The top view shows a 100mm x 100mm plate with a central 20mm x 20mm square hole. The front view shows the plate's thickness of 10mm and a central 20mm x 20mm square hole. The side view shows the plate's width of 100mm and a central 20mm x 20mm square hole. The drawing also includes dimensions for the hole patterns: 22.00mm for the top hole pattern, 28.45mm for the bottom hole pattern, and 20.00mm for the side hole pattern. The hole diameter is specified as $\phi 1.40$ (建议孔径尺寸).

☞ SUPU ID	MC-DPA5.0V28-F-0002
☞ Pitch	5.0
☞ Number of connections	28
☞ Connection method	-

☞ Protection Level	IP20
☞ Operating temperature range	-40~+105°C
☞ Insulation material	PA66
☞ Insulation material group	I
☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	320V
☞ IEC Rated Voltage	10A
☞ Overvoltage category	III III II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	4.0KV 4.0KV 4.0KV
☞ UL Rated Current	15A - 10A
☞ UL Rated Voltage	300V - 300V
☞ Conductor cross section rigid	-
☞ Conductor cross section flexible	-
☞ Conductor cross section flexible,with furrule	-
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	-
☞ Stripping length	-
☞ Use group	B/C/D

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat