



Product Type: Plug-in terminal-Socket

Product Name:MC-DPA5.0V36-
F-0002

Product Description: Pitch:5.0mm Rated

Voltage : 320V Rated Current:10A

colour : customizable

Product Size



Parameters

⌘ SUPU ID	MC-DPA5.0V36-F-0002	
⌘ Pitch		5.0
⌘ Number of connections		36
⌘ Connection method		-
⌘ Protection Level		IP20
⌘ Operating temperature range		-40~+105°C
⌘ Insulation material		PA66
⌘ Insulation material group		I

☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Color	Green/Black/Blue/Grey/Orange/Red

Technical data

☞ IEC Rated Current	320V
☞ IEC Rated Voltage	10A
☞ Overvoltage category	III III II
☞ Degree of pollution	3 2 2
☞ Rated impulse voltage	4.0KV 4.0KV 4.0KV
☞ UL Rated Current	15A - 10A
☞ UL Rated Voltage	300V - 300V
☞ Conductor cross section rigid	-
☞ Conductor cross section flexible	-
☞ Conductor cross section flexible,with furrule	-
☞ Locking screw Specification	-
☞ Locking screw torque	-
☞ Fixed Screw Specification	-
☞ Stripping length	-
☞ Use group	B/C/D

Commercial data

☞ Order No	MC-DPA5.0V36-F-0002
------------	---------------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-08-19 16:52

The right to modify data belongs to SUPU.