



Product Type: Plug-in terminal-Socket

## Product Name:MC-DPT3.5H24-BK-2000

Product Description: Pitch:3.5mm Rated

Voltage : 160V Rated Current:8A

colour : customizable

### Product Size



### Parameters

|                                                                                                          |                      |
|----------------------------------------------------------------------------------------------------------|----------------------|
|  SUPU ID               | MC-DPT3.5H24-BK-2000 |
|  Pitch                 | 3.5                  |
|  Number of connections | 24                   |
|  Connection method     | -                    |

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn,Plated                        |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|                                                 |               |
|-------------------------------------------------|---------------|
| ☞ IEC Rated Current                             | 160V          |
| ☞ IEC Rated Voltage                             | 8A            |
| ☞ Overvoltage category                          | III III II    |
| ☞ Degree of pollution                           | 3 2 2         |
| ☞ Rated impulse voltage                         | - 2.5KV 2.5KV |
| ☞ UL Rated Current                              | 8A - -        |
| ☞ UL Rated Voltage                              | 150V - -      |
| ☞ Conductor cross section rigid                 | -             |
| ☞ Conductor cross section flexible              | -             |
| ☞ Conductor cross section flexible,with furrule | -             |
| ☞ Locking screw Specification                   | -             |
| ☞ Locking screw torque                          | -             |
| ☞ Fixed Screw Specification                     | -             |
| ☞ Stripping length                              | -             |
| ☞ Use group                                     | B/C/D         |

☞ Order No

MC-DPT3.5H24-BK-2000

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-09-18 20:50

The right to modify data belongs to SUPU.