



Product Type: Push-in spring terminal

Product Name:

Product Description: Push-in terminal block
TPDS2.5-4-PV,Rail-mounted push-in terminal
block,Manufacturer of rail-mounted push-in
terminal block

Parameters

☞ SUPU ID	-5°C~70°C
☞ Width	-25°C~60°C
☞ Number of levels	30%~70%
☞ Number of connections	PA66
☞ Connection method	I
☞ Protection Level	V0
☞ Insulation material	III
☞ Insulation material group	3
☞ Contact material	0.2-4mm ²
☞ Contact plating	0.2-2.5mm ²
☞ Ambient temperature (operation)	Copper alloy
☞ Ambient temperature (assembly)	Sn,Plated
☞ Ambient temperature (storage)	20A
☞ Permissible humidity (storage/transport)	800V

Technical data

⌘ IEC Rated Current	0.2-2.5mm ²
⌘ IEC Rated Voltage	8-10mm
⌘ Overvoltage category	B/C
⌘ Degree of pollution	20A
⌘ Rated impulse voltage	600V
⌘ UL Rated Current	TPDS2.5-4-XX-EC,TJA5.2-XX,WS-TP2.5-5,305801,TMZ9.6-50,TMBWT5.2-72
⌘ UL Rated Voltage	TPDS2.5-4-GY,TPDS2.5-4-PE
⌘ Conductor cross section rigid	26-12AWG
⌘ Conductor cross section flexible	Multi-level feed-through terminal block
⌘ Conductor cross section flexible,with furrule	900401
⌘ Stripping length	900421/011
⌘ Use group	900421/031

Commercial data

⌘ Order No	The rail-mounted push-in terminal block TPDS2.5-4-PV produced by Supu Electronics adopts Push-in connection technology, easy and convenient to operate, it is an important electronic connection technology that achieves reliable electrical connections. Learn more now or contact us for customized solutions.
⌘ Packing unit	CE
⌘ Minimum order quantity	TPDS2.5-4-PV
⌘ Weight per unit (without packaging)	5.2mm
⌘ Single piece weight	2

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-10-28 00:23

The right to modify data belongs to SUPU.