



Product Type: Push-in spring terminal

Product Name:TP2.5-2-2-PE

Product Description: Connection method:Push-in connection,Number of connections:2,Number of levels : 1

Product Size



Parameters

⌘ SUPU ID	TP2.5-2-2-PE	
⌘ Width		5.2mm
⌘ Number of levels		1
⌘ Number of connections		2
⌘ Connection method	Push-in connection	
⌘ Protection Level		IP20
⌘ Insulation material		PA66
⌘ Insulation material group		I

☞ Contact material	Copper alloy
☞ Contact plating	Sn,Plated
☞ Ambient temperature (operation)	-40°C~105°C
☞ Ambient temperature (assembly)	-5°C~70°C
☞ Ambient temperature (storage)	-25°C~60°C
☞ Permissible humidity (storage/transport)	30%~70%

Technical data

☞ IEC Rated Current	/
☞ IEC Rated Voltage	/
☞ Overvoltage category	III
☞ Degree of pollution	3
☞ Rated impulse voltage	6KV
☞ UL Rated Current	/
☞ UL Rated Voltage	/
☞ Conductor cross section rigid	/
☞ Conductor cross section flexible	/
☞ Conductor cross section flexible,with furrule	/
☞ Stripping length	/
☞ Use group	/
☞ Rated cross section	/

Commercial data

☞ Order No	TP2.5-2-2-PE
------------	--------------

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

Date:2025-10-27 13:24

The right to modify data belongs to SUPU.