





Product Type: Push-in spring terminal

**Product Name:TP2.5-3-1-GY**

Product Description: Connection method:Push-in connection,Number of connections:3,Number of levels : 1

Product Size



Parameters

|                             |                    |       |
|-----------------------------|--------------------|-------|
| ⌘ SUPU ID                   | TP2.5-3-1-GY       |       |
| ⌘ Width                     |                    | 5.2mm |
| ⌘ Number of levels          |                    | 1     |
| ⌘ Number of connections     |                    | 3     |
| ⌘ Connection method         | Push-in connection |       |
| ⌘ Protection Level          |                    | IP20  |
| ⌘ Insulation material       |                    | PA66  |
| ⌘ Insulation material group |                    | I     |

|                                            |              |
|--------------------------------------------|--------------|
| ☞ Contact material                         | Copper alloy |
| ☞ Contact plating                          | Sn,Plated    |
| ☞ Ambient temperature (operation)          | -40°C~105°C  |
| ☞ Ambient temperature (assembly)           | -5°C~70°C    |
| ☞ Ambient temperature (storage)            | -25°C~60°C   |
| ☞ Permissible humidity (storage/transport) | 30%~70%      |

## Technical data

|                                                 |                        |
|-------------------------------------------------|------------------------|
| ☞ IEC Rated Current                             | 24A                    |
| ☞ IEC Rated Voltage                             | 500V                   |
| ☞ Overvoltage category                          | III                    |
| ☞ Degree of pollution                           | 3                      |
| ☞ Rated impulse voltage                         | 6KV                    |
| ☞ UL Rated Current                              | 20A                    |
| ☞ UL Rated Voltage                              | 300V                   |
| ☞ Conductor cross section rigid                 | 0.2-4mm <sup>2</sup>   |
| ☞ Conductor cross section flexible              | 0.2-2.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with furrule | 0.2-2.5mm <sup>2</sup> |
| ☞ Stripping length                              | 8-10mm                 |
| ☞ Use group                                     | B/C                    |
| ☞ Rated cross section                           | 26-12AWG               |

## Commercial data

|            |              |
|------------|--------------|
| ☞ Order No | TP2.5-3-1-GY |
|------------|--------------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

---

Date:2025-10-27 13:34

The right to modify data belongs to SUPU.