



Product Type: Fixed terminal

**Product Name:235324-010**

Product Description: Pitch:7.5mm Rated

Voltage : 630V Rated Current:17.5A Connection

method : Push-in spring connection

colour : customizable

Product Size



Parameters

|                               |                    |
|-------------------------------|--------------------|
| ⌘ SUPU ID                     | 235324/010         |
| ⌘ Pitch                       | 7.5                |
| ⌘ Number of levels            | Single layer       |
| ⌘ Number of connections       | 24                 |
| ⌘ Connection method           | Push in connection |
| ⌘ Protection Level            | IP20               |
| ⌘ Operating temperature range | -40~+105°C         |
| ⌘ Insulation material         | PA66               |

|                             |                                  |
|-----------------------------|----------------------------------|
| ☞ Insulation material group | I                                |
| ☞ Contact material          | Copper alloy                     |
| ☞ Contact plating           | Sn,Plated                        |
| ☞ Color                     | Green/Black/Blue/Grey/Orange/Red |

## Technical data

|                                                 |                        |
|-------------------------------------------------|------------------------|
| ☞ IEC Rated Current                             | 17.5A                  |
| ☞ IEC Rated Voltage                             | 630V                   |
| ☞ Overvoltage category                          | III/III/ II            |
| ☞ Degree of pollution                           | 3 2 2                  |
| ☞ Rated impulse voltage                         | 6.0KV 6.0KV 6.0KV      |
| ☞ UL Rated Current                              | 10A - 10A              |
| ☞ UL Rated Voltage                              | 300V - 300V            |
| ☞ Conductor cross section rigid                 | 0.2-2.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 0.2-2.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with furrule | 0.2-2.5mm <sup>2</sup> |
| ☞ Locking screw Specification                   | -                      |
| ☞ Locking screw torque                          | -                      |
| ☞ Fixed Screw Specification                     | -                      |
| ☞ Stripping length                              | 9-10mm                 |

## Commercial data

|            |            |
|------------|------------|
| ☞ Order No | 235324/010 |
|------------|------------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat

---

Date:2025-11-11 22:11

The right to modify data belongs to SUPU.