

Product Type: Fixed terminal

Product Name:235417

Product Description: Pitch:10mm Rated Voltage：1000V Rated Current:17.5A Connection method：Push-in spring connection colour：customizable

Product Size



Parameters

SUPU ID	235417
Pitch	10
Number of levels	Single layer
Number of connections	17
Connection method	Push in connection
Protection Level	IP20
Operating temperature range	-40~+105°C
Insulation material	PA66

Insulation material group	I
Contact material	Copper alloy
Contact plating	Sn,Plated
Color	Green/Black/Blue/Grey/Orange/Red

Technical data

IEC Rated Current	17.5A
IEC Rated Voltage	1000V
Overvoltage category	III/III/ II
Degree of pollution	3 2 2
Rated impulse voltage	8.0KV 8.0KV 8.0KV
UL Rated Current	10A - 10A
UL Rated Voltage	300V - 300V
Conductor cross section rigid	0.2-2.5mm²
Conductor cross section flexible	0.2-2.5mm²
Conductor cross section flexible,with furrule	0.2-2.5mm²
Locking screw Specification	-
Locking screw torque	-
Fixed Screw Specification	-
Stripping length	9-10mm

Commercial data

Order No	235417

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336

Wechat

The right to modify data belongs to SUPU.