

Product Type: Plug-in terminal-Plug

Product Name:MC-RF3.81H09P-K-0001

Product Description: Pitch:3.81mm Rated Voltage：160V Rated Current:8A Connection method：Push in connection

colour：customizable

Product Size





Parameters

SUPU ID	MC-RF3.81H09P-K-0001
Pitch	3.81
Number of levels	single layer
Number of connections	9

Connection method	Push in connection
Protection Level	IP20
Operating temperature range	-40~+105°C
Insulation material	PA66
Insulation material group	I
Contact material	Copper alloy
Contact plating	Sn,Plated
Color	Green/Black/Blue/Grey/Orange/Red

Technical data

IEC Rated Current	8A
IEC Rated Voltage	160V
Overvoltage category	III/III/ II
Degree of pollution	3 2 2
Rated impulse voltage	2.5KV 2.5KV2.5KV
UL Rated Current	8A 8A -
UL Rated Voltage	150V 50V -
Conductor cross section rigid	0.2-1.5mm²
Conductor cross section flexible	0.2-1.5mm²
Conductor cross section flexible,with furrule	0.2-1.5mm²
Locking screw Specification	-
Locking screw torque	-
Fixed Screw Specification	-
固定螺钉扭矩	-

Stripping length	10mm
Use group	B/C/D
Rated cross section	24~16AWG

Commercial data

Order No	MC-RF3.81H09P-K-0001

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336

Wechat

The right to modify data belongs to SUPU.