





Product Type: Plug-in terminal-Socket

Product Name:458415-010

Product Description: Pitch:5.08mm Rated

Voltage : 320V Connection method : Spring cage  
connection colour : orange

## Product Size



## Parameters

|                                                                                                          |              |
|----------------------------------------------------------------------------------------------------------|--------------|
|  SUPU ID               | 458415-010   |
|  Pitch                 | 5.08         |
|  Number of levels      | Single layer |
|  Number of connections | 15           |

|                               |                        |
|-------------------------------|------------------------|
| ☞ Connection method           | Spring cage connection |
| ☞ Protection Level            | IP20                   |
| ☞ Operating temperature range | -40~+105°C             |
| ☞ Insulation material         | PA66                   |
| ☞ Insulation material group   | I                      |
| ☞ Contact material            | Copper alloy           |
| ☞ Contact plating             | Sn,Plated              |
| ☞ Color                       | Orange                 |

### Technical data

|                                                 |                        |
|-------------------------------------------------|------------------------|
| ☞ IEC Rated Current                             | 320V                   |
| ☞ IEC Rated Voltage                             | 16A                    |
| ☞ Overvoltage category                          | III III II             |
| ☞ Degree of pollution                           | 3 2 2                  |
| ☞ Rated impulse voltage                         | 4.0KV 4.0KV 4.0KV      |
| ☞ UL Rated Current                              | 15A - 10A              |
| ☞ UL Rated Voltage                              | 300V - 300V            |
| ☞ Conductor cross section rigid                 | 0.2-2.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible              | 0.2-2.5mm <sup>2</sup> |
| ☞ Conductor cross section flexible,with furrule | 0.2-2.5mm <sup>2</sup> |
| ☞ Locking screw Specification                   | -                      |
| ☞ Locking screw torque                          | -                      |
| ☞ Fixed Screw Specification                     | -                      |
| ☞ 固定螺钉扭矩                                        | -                      |

|                       |          |
|-----------------------|----------|
| ☞ Stripping length    | 8-9mm    |
| ☞ Use group           | B/C/D    |
| ☞ Rated cross section | 24~14AWG |

## Commercial data

|            |            |
|------------|------------|
| ☞ Order No | 458415-010 |
|------------|------------|

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat