



Product Type: Fixed terminal

Product Name:MC-TC7.5H5P-0001


Product Description: Pitch:7.5mm Rated


Voltage: 1000V Rated Current:41A Connection


method: Push-in spring connection

colour: customizable

Product Size







Parameters

₩ SUPU ID MC-TC7.5H5P-0001

See Pitch 7.5

Single layer Single layer

% Number of connections 5

Connection method	Push in connection
86 Protection Level	IP20
86 Operating temperature range	-40~+105°C
SS Insulation material	PA66
So Insulation material group	
Se Contact material	Copper alloy
Se Contact plating	Sn,Plated
86 Color	Green/Black/Blue/Grey/Orange/Red
Technical data	
Se IEC Rated Current	41A
₩ IEC Rated Voltage	1000V
Overvoltage category	111/111/11
Degree of pollution	322
Rated impulse voltage	6.0KV 6.0KV 6.0KV
88 UL Rated Current	36A 36A 5A
₩ UL Rated Voltage	300V 150V 600V
Conductor cross section rigid	0.2~10mm²
86 Conductor cross section flexible	0.2~10mm²
Conductor cross section flexible, with furrule	0.2~10mm²
86 Locking screw Specification	-
86 Locking screw torque	-
Rixed Screw Specification	-
88 Stripping length	13-15mm

36 Order No MC-TC7.5H5P-0001

Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,

Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn Service Hotline: 400-626-6336



Wechat

Date:2025-07-31 03:25

The right to modify data belongs to SUPU.