





Product Type: Plug-in terminal-Plug

Product Name:MC-RU5.08SV22-F-0001

Product Description: Pitch:5.08mm Rated  
Voltage : 320V Rated Current:16A  
colour : customizable

## Product Size



## Parameters

|                                                                                                          |                      |
|----------------------------------------------------------------------------------------------------------|----------------------|
|  SUPU ID               | MC-RU5.08SV22-F-0001 |
|  Pitch                 | 5.08                 |
|  Number of levels      | single layer         |
|  Number of connections | 22                   |

|                               |                                  |
|-------------------------------|----------------------------------|
| ☞ Connection method           | -                                |
| ☞ Protection Level            | IP20                             |
| ☞ Operating temperature range | -40~+105°C                       |
| ☞ Insulation material         | PA66                             |
| ☞ Insulation material group   | I                                |
| ☞ Contact material            | Copper alloy                     |
| ☞ Contact plating             | Sn,Plated                        |
| ☞ Color                       | Green/Black/Blue/Grey/Orange/Red |

### Technical data

|                                    |             |
|------------------------------------|-------------|
| ☞ IEC Rated Current                | 16A         |
| ☞ IEC Rated Voltage                | 320V        |
| ☞ Overvoltage category             | III/III/ II |
| ☞ Degree of pollution              | 3 2 2       |
| ☞ Rated impulse voltage            | 4KV 4KV 4KV |
| ☞ UL Rated Current                 | 16A - 10A   |
| ☞ UL Rated Voltage                 | 250V - 300V |
| ☞ Conductor cross section rigid    | -           |
| ☞ Conductor cross section flexible | -           |
| ☞ Fixed Screw Specification        | M2.5        |
| ☞ 固定螺钉扭矩                           | 0.3N.M      |
| ☞ Stripping length                 | -           |
| ☞ Use group                        | B/C/D       |
| ☞ Rated cross section              | -           |

## Ningbo SUPU Electronics Co., Ltd.

Address: No. 150, Xinxing 4th Road, High-tech Industrial Development Zone,  
Cixi City, Zhejiang Province, China

Zip code: 315303

Switchboard: +86 574-63288158

Fax: +86 574-63288170

E-mail:supucontact@supu.cn

Service Hotline: 400-626-6336



Wechat